Corning[®] LSE[™] Platform Rocker

Ideal for blotting and staining applications





The Corning LSE Platform Rocker is a compact yet high capacity rocker that is ideal for western blotting and general mixing applications. The adjustable rocking speed and fixed 7 degree tilt makes it optimal for staining fragile gels, as well as the more intensive action necessary for washing blots.

The speed of the Corning Platform Rocker can be adjusted from 2 to 60 rpm and the timer can be set for up to 2 hours or for continuous operation. The unit is safe to use in temperature controlled environments up to 70°C and is available in single or high capacity double platform configurations. Both of these rugged models come with a 5-year warranty.

Features and Benefits

- Low profile and compact size
- ▶ 11-pound (5 kg) load capacity
- Non-slip rubber pads to prevent sample containers from moving during operation
- Double platform model available for increased capacity



Specifications

Speed Settings	5 to 120 tilts/minute
Timer	0 to 2 hours or continuous
Motion	Rocking
Tilt Angle	Fixed 7°
Maximum Load	11 lb. (5 kg)
Ambient Operation Range	+4°C to 70°C
Dimensions	12.8 x 14.2 x 5.7 in. (32.5 x 36 x 14.5 cm)
Weight	Single Platform: 11.7 lb. (5.3 kg) Double Platform: 12.7 lb. (5.8 kg)
Electrical	115V, 50/60Hz 230V, 50/60Hz
Warranty	5 years
Platform Size	11.8 x 11.8 in. (30 x 30 cm)

Ordering Information

Corning® LSE™ Platform Rockers

Cat. No.	Description	Qty/Cs
6703	Corning LSE Platform Rocker, single platform, 115V	1
6704	Corning LSE Platform Rocker, single platform, 230V	1
6705	Corning LSE Platform Rocker, double platform, 115V	1
6706	Corning LSE Platform Rocker, double platform, 230V	1

For more specific information on claims, visit the Certificates page at www.corning.com/lifesciences.

Warranty/Disclaimer: Unless otherwise specified, all products are for research use only. Not intended for use in diagnostic or therapeutic procedures. Corning Life Sciences makes no claims regarding the performance of these products for clinical or diagnostic applications.

For additional product or technical information, visit **www.corning.com/lifesciences** or call 800.492.1110. Outside the United States, call +1.978.442.2200 or contact your local Corning sales office.

CORNING

Corning Incorporated *Life Sciences*

836 North St. Building 300, Suite 3401 Tewksbury, MA 01876 t 800.492.1110 t 978.442.2200 f 978.442.2476

www.corning.com/lifesciences

ASIA/PACIFIC Australia/New Zealand t 61 427286832

China t 86 21 3338 4338 f 86 21 3338 4300 India

India t 91 124 4604000 f 91 124 4604099 Japan t 81 3-3586 1996 f 81 3-3586 1291 Korea

t 82 2-796-9500 f 82 2-796-9300 Singapore t 65 6572-9740 f 65 6861-2913

Taiwan t 886 2-2716-0338 f 886 2-2516-7500

EUROPE CSEurope@corning.com

France t 0800 916 882 f 0800 918 636 Germany t 0800 101 1153 f 0800 101 2427

The Netherlands t 020 655 79 28 f 020 659 76 73

United Kingdom t 0800 376 8660 f 0800 279 1117

All Other European Countries t +31 (0) 206 59 60 5

t +31 (0) 206 59 60 51 f +31 (0) 206 59 76 73

LATIN AMERICA grupoLA@corning.com

Brasil t 55 (11) 3089-7400

Mexico t (52-81) 8158-8400